

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 888 174 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

24.10.2001 Bulletin 2001/43

(51) Int Cl.7: **B01J 8/18, B01J 8/26,
B01J 8/00, C07C 5/333,
C07C 11/00, C07C 2/84,
C10G 11/18**

(21) Application number: **97937611.8**

(22) Date of filing: **01.09.1997**

(86) International application number:
PCT/FI97/00509

(87) International publication number:
WO 98/08600 (05.03.1998 Gazette 1998/09)

(54) **METHOD AND APPARATUS BASED ON A FLUIDIZED-BED REACTOR FOR CONVERTING
HYDROCARBONS**

**METHODE UND VORRICHTUNG BASIEREND AUF EINEM WIRBELBETTREAKTOR ZUR
KOHLENWASSERSTOFFUMWANDLUNG**

**PROCEDE ET DISPOSITIF BASES SUR UN REACTEUR A LIT FLUIDISE POUR TRANSFORMER
DES HYDROCARBURES**

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB IT LI LU NL PT SE

(30) Priority: **30.08.1996 FI 963404**

(43) Date of publication of application:
07.01.1999 Bulletin 1999/01

(73) Proprietor: **Fortum Oil and Gas Oy**
02150 Espoo (FI)

(72) Inventors:
• **RUOTTU, Seppo**
FIN-48800 Karhula (FI)

• **KÄÄRIÄNEN, Karl**
FIN-01300 Vantaa (FI)
• **HILTUNEN, Jyrki**
FIN-04130 Sipoo (FI)

(74) Representative: **Sundman, Christoffer et al**
Seppo Laine Oy,
Itämerenkatu 3 B
00180 Helsinki (FI)

(56) References cited:
GB-A- 2 240 285 **US-A- 2 358 497**
US-A- 2 514 288 **US-A- 2 525 925**
US-A- 4 152 393

EP 0 888 174 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The invention relates to a method according to the preamble of claim 1 for converting hydrocarbons.

[0002] According to the present method, a gaseous or liquid hydrocarbon feed to be processed is admitted into a reactor operated with a circulating mass of solids kept in a fluidized state (later called a "fluidized-bed reactor"), where it undergoes conversion at an elevated temperature in the presence of a fluidized solids medium capable of stabilizing the energy balance of the conversion process.

[0003] The invention also concerns an apparatus according to the preamble of claim 12 for processing and converting hydrocarbons.

[0004] Generally, fluidized-bed reactors are used in the conversion processes of hydrocarbons. Herein, a catalyst or similar particulates suited for heat exchange and fluidization is kept in a fluidized state by the upward flow of a gaseous hydrocarbon. Typically, the minimum fluidization flow is provided by means of a pre-fluidizing gas such as steam or recirculation of the product gas. In conventional fluidized-bed reactors operated with the linear flow rate of the medium adjusted close to the minimum fluidization flow rate, the particulate matter remains in the fluidized bed of the reactor, instead of becoming carried over from the reactor in significant amounts along with the hydrocarbon flow.

[0005] By contrast, at flow rates appreciably higher than the minimum fluidization flow rate, the upper surface of the fluidized bed becomes less defined, in fact, forming a zone in which the solids content decreases along the vertical axis. At sufficiently high flow rates this effect leads to a situation in which practically all the particulate matter will be carried over along with the hydrocarbon flow maintaining the fluidized state. Then, the solids must be separated from the hydrocarbon outlet flow leaving the reactor by means of cyclones and are recirculated either directly or via a regenerator back to the bottom section of the reactor. Such a system is called either a circulating fluidized bed (CFB), or analogously, a circulating fluidized bed reactor (CFBR) if a chemical reaction occurs in the suspended solids.

[0006] One of the most generally used reactor systems in the art for catalytic cracking of hydrocarbons is the FCC equipment comprising chiefly a riser tube (reactor) operated in the fast fluidization flow state, cyclone separators of the catalyst from the reaction product that are operated in a diluted suspension phase and a large-volume regenerator operated in the fluidized-bed state. An example of such FCC equipment is represented by the embodiment illustrated in US Pat. No. 4,957,617.

[0007] Other applications utilizing catalytic fluidized-bed reactors are, e.g.,:

- catalytic reforming,
- preparation of phthalic acid anhydride or maleic acid anhydride,
- oxidative dimerization of methane,
- Fischer-Tropsch synthesis,
- dehydrogenation,
- chlorination and bromination of methane, ethane and similar alkanes, and
- conversion of methanol into olefins or gasoline.

[0008] Noncatalytic processes using fluidized-bed reactors are, e.g.,:

- thermal cracking,
- catalyst regeneration, and
- gasification processes.

[0009] Suitable physical processes are, e.g.,:

- drying,
- heat exchange between two gases, and
- adsorption.

[0010] Of the above-listed processes, significant economical values pertain particularly to catalytic cracking, dehydrogenation, the Fischer-Tropsch synthesis, methanol conversion process to olefins (MTO) and possibly the process for oxidative dimerization of methane which still is at an experimental stage.

[0011] Conventional reaction environments have certain essential drawbacks. For instance, the reaction time of a conventional fluidized-bed reactor is difficult to control, and the erosion of the catalyst/solids and reactor structures is a major equipment complication. These problems are accentuated particularly when the process control presumes a short residence time combined with a high process temperature. In chemical reactors based on a scaled design, the residence times of both the gas and the solids must remain unchanged. However, with a larger reactor diameter, the residence time of solids in the reactor tends to become longer, because the reflux of the solids close to the walls

increases. To counter this effect, the flow rate must be increased, which further requires a higher reactor to keep the gas residence time unchanged.

[0012] Apparatuses for separation of gas from solids/catalyst particulates that forms an essential part of process equipment are also hampered by problems discussed in detail below:

[0013] Particulate matter and product gas leaving the reactor are separated from each other in cyclone separators utilizing centrifugal force. Generally, cyclones have a single-port structure, i.e., they have only one inlet nozzle for the particulate matter suspension. In practice, the maximum diameter of single-port cyclones is about 1 m, whereby due to flow capacity requirements a plurality of cyclones must be connected in parallel, and further, two or three in series in the direction of the gas flow.

[0014] A cyclone is rated effective if it can separate small particles of less than 15 μm diameter from the gas flow. Conventionally, cyclone separators have either a coiled or spiralled structure. The particulate matter suspension is directed as a tangential flow into the cylindrical section of the cyclone, whereby the solids are separated under the centrifugal force as the flow circulates in the cyclone typically 7-9 revolutions within the cylindrical section and the conical section forming a continuation thereof. Also axial cyclones are known in which the gas flowing through a tube is forced into a circulating motion by means of vanes, whereby the solids under the centrifugal force are driven against the tube wall and separated thereon from the gas flow. The most common cyclone type is the so-called Zenz cyclone, in which the proportions of the different parts of the cyclone are standardized permitting the design of the cyclone to be based on graphs and computational formulas. The separation efficiency of the cyclone is enhanced by a large number of flow revolutions in the cyclone chamber, high flow rate at the inlet nozzle, high density of solids, small cross section of the inlet nozzle port and low viscosity of the gas.

[0015] In conventional single-port cyclones, the solids flow impinges on the cyclone inner wall as a homogeneous gas-suspended jet of high flow velocity which in primary cyclones is typically in the range 20-25 m/s, in secondary cyclones about 35 m/s, and in tertiary cyclones about 40 m/s. The flow rate of the impinging jet must be high, because the cyclone inlet nozzle width (jet width) is generally, e.g., in standardized Zenz cyclones about one-fourth of the cyclone diameter, and the particulate matter must be brought over the entire width of the impinging jet close to the cyclone inner wall in order to achieve separation of the solids. In this type of cyclones, the point most susceptible to erosion is the area of the cyclone inner wall receiving the impact of the suspended solids jet.

[0016] It is an object of the present invention to overcome the drawbacks of the above-described prior-art technology and to implement fluidization in a novel type of fluidized-bed reactor offering maximized efficiency of lateral mixing. It is a further object of the invention to provide a reactor structure in which the solids after the reaction are separated with a maximum speed and efficiency from the product gases.

[0017] According to the invention, the conversion of hydrocarbons is performed in a circulating fluidized-bed reactor in which the reaction space, i.e., the fluidization space of the reactor comprises an intershell space of axially annular cross section remaining between two concentrically located cylinders or cones, in which space the feed, typically in the liquid phase, is first vaporized and subsequently converted into reaction products at an elevated temperature in the presence of particulate matter, which may additionally have catalytic properties. The feed may alternatively be in a gaseous phase. After leaving the reactor, the reaction product is generally distilled or purified by other methods into usable fractions. The novel reactor is suitable for, i.a., catalytic and thermal cracking, dehydrogenation and oxidizing dimerization of methane.

[0018] Further according to the invention, the particulate matter is separated from the reaction gas by means of a multi-inlet (in the following also "multiport") cyclone, which is located directly above the axially annular reactor riser space. This arrangement makes it possible to shorten the residence time of the reaction, because a multiport cyclone offers faster and more efficient separation of particulate matter from the reaction gas flow over a single-port cyclone. From the cyclone, the particulate matter can be recirculated to a regenerator via a solids return channel, or the downward return leg, which is formed by an intershell space of axially annular cross section remaining between two concentrically located cylinders or cones.

[0019] More specifically, the method according to the invention is characterized by what is stated in the characterizing part of claim 1.

[0020] Furthermore, the apparatus according to the invention is characterized by what is stated in the characterizing part of claim 12.

[0021] In the description of the present invention, the term "residence time" refers to the mean residence time of hydrocarbon molecules from the infeed point of the reactor to the cyclone outlet tube, said time varying in the range 0.05 - 10 s, typically 0.1 - 5 s, and the term "elevated temperature" refers to a temperature range of 100 - 1000 °C. The reactor is suited for the following processes and others: catalytic and thermal cracking, dehydrogenation, Fischer-Tropsch synthesis, preparation of maleic acid anhydride and oxidative dimerization of methane.

[0022] The term "reaction product" is used to refer to products resulting from the above-mentioned processes. Accordingly, the reaction products may contain, e.g., cracking and dehydrogenation products chiefly comprising light olefins such as propene, n-butenes, isobutene and amylenes.

[0023] The term "solids" is used to refer to the particulate matter which forms a suspension in the reaction space. The particulate matter typically comprises solid catalyst particles if the reactor is used for catalytic reactions. When the reactor is used for thermal processes, the particulate matter is formed by inert particles serving to transfer heat or material into the reaction space or away therefrom. The catalyst is selected to suit the process. Accordingly, catalytic cracking typically uses natural or synthetic aluminum silicates, zeolites and alumina. Conventional zeolites include zeolites X and Y which can be stabilized by lanthanides. Dehydrogenation processes use chromium-aluminum oxide catalysts, for instance.

[0024] Generally, the invention is most appropriately applied to high-temperature endo- and exothermic processes requiring a short residence time such as catalytic or thermal cracking, dehydrogenation, Fischer-Tropsch synthesis, MTO and oxidative dimerization of methane. According to a first preferred embodiment, the reactor according to the invention is used for catalytic cracking, wherein the reactor feed may be light gas oil, heavy gas oil or light bottom oil in order to produce light olefins and/or gasoline. In cracking, the process temperature is about 520 - 650 °C and the residence time in the range 0.5 - 5 s.

[0025] According to a second preferred embodiment, the reactor according to the invention is used for thermal cracking, wherein bottom oil or other heavy hydrocarbon is fed into the reactor for cracking into lighter hydrocarbon fractions. The process temperature is 650 - 1000 °C and the residence time in the range 0.2 - 0.5 s.

[0026] According to a third preferred embodiment, the reactor is used in the dehydrogenization of a feed comprising pentanes, isobutane, n-butane, propane or a mixture thereof at a process temperature of 650 - 750 °C and a residence time in the range 0.4 - 2 s in order to prepare amylenes, isobutene, n-butenes, propene or mixtures thereof.

[0027] According to a fourth preferred embodiment, the reactor is used for oxidative dimerization of methane in natural gas feed at a process temperature of 800 - 900 °C and a residence time in the range 0.08 - 0.3 s.

[0028] According to a fifth preferred embodiment, the reactor feed comprising hydrocarbons is gasified, that is, partially oxidized, with air or other oxygen-containing gas into synthesis gas, that is, gas containing at least carbon monoxide and hydrogen. Partial thermal oxidization occurs at 1000 - 1300 °C and partial catalytic oxidization at 700 - 1000 °C with a residence time essentially sufficient to achieve a chemical reaction equilibrium. In order to increase the proportion of hydrogen in the produced synthesis gas and to achieve thermal equilibrium, steam may additionally be introduced into the reaction.

[0029] Next, the invention will be examined closer with the help of a detailed description and a few exemplifying embodiments, whose equipment constructions are elucidated by making reference to appended drawings in which:

Fig. 1 is a side view of a preferred embodiment of the structure of an apparatus particularly well suited for use in catalytic cracking and heat exchange processes; and

Fig. 2 is a side view of the basic structure of a simplified reactor embodiment according to the invention.

[0030] A reactor according to the invention suited for conversion of hydrocarbons, generally from a feed of paraffinic hydrocarbons in a circulating bed reactor, principally comprises a reaction space formed between two concentrically located upright cylinders or cones, whereby the reaction space and the downward return leg has an axially annular cross section. The infeed nozzles, through which the liquid or, in certain cases, gaseous feed is passed into the reaction space, are located in the bottom section of the reaction space. The feed nozzles are normally aligned upward. The inert solids or catalyst is taken along a downward return leg, which in an axially annular fashion surrounds the reactor, to the bottom section of the reactor via an annular port provided in the outer shell of the reactor, or alternatively, via a number of smaller openings made to said reactor outer shell. The solids flow rate into the reactor can be advantageously controlled by means of a cylinder adapted about the reactor outer shell, whereby the rotation or elevation of said cylinder allows throttling of the solids inlet port. Conventional valves may also be used for controlling the solids flow from the downward return leg back to the reactor.

[0031] In such a preferred embodiment of the invention in which a reactor according to the invention is used for catalytic cracking, the reactor may be adapted concentric with another reactor. Then, the inner reactor of the two is used as a cracking reactor, while the outer serves as a regenerator in which the catalyst is regenerated and heated to a desired temperature. From the reactor proper, the catalyst is transferred to the regenerator via the axially annular outlet channel, or downward return leg, and channels made to the fluidization space of the reactor. The downward return leg, also known as the catalyst return channel to the reactor, forms a space of axially annular cross section.

[0032] The solids flow into the reaction space via the solids inlet port and will be mixed in the axially annular riser of the reactor with the upward prefluidizing gas flow in which the solids pass in the axially annular riser to the level of the feed inlet nozzles. Here, the liquid feed, which is atomized into small droplets, is vaporized and heated to the reaction temperature as it meets the hot upward flow of the particulate matter. Due to the feed vaporization, the solids flow velocity will increase. As the flow velocity is substantially higher than the minimum fluidization velocity, the solids will follow the gas flow, however, at a velocity slightly lower than the gas flow velocity. A separating unit formed by a multiport

cyclone of the reactor, which is placed to the upper end of the reaction space, performs separation of particulates from the solids suspension. From the cyclone, the solids are passed after regeneration back to the reactor via the axially annular downward return leg surrounding the reactor riser. The reaction product gases are removed via the central tube of the cyclone.

[0033] The riser channel with the axially annular cross section can be formed between, e.g., two concentric cylindrical surfaces of revolution, whereby the inner surface of the outer cylindrical shell forms the outer wall of the reaction space and the outer surface of the inner cylindrical shell forms the inner wall of the reaction space. Hence, a reactor construction according to the invention formed from two concentrically erected cylindrical shells results in a compact, sturdy and easy-to-install reactor structure.

[0034] In the vertical direction, the axially annular cross section of the reactor riser space can be made constant, whereby the spacing of the reactor walls formed by upright cylindrical or conical shells is unchanged throughout the height of the reactor riser. Alternatively, the reactor cross section can be made variable as a function of the height coordinate, which option can be utilized to affect the fluidization characteristics of the reactor.

[0035] When desired, the reactor riser space may be divided axially into concentric segments. Such segmental division can be implemented by installing additional concentric cylindrical or spiralling baffles in the reaction space formed between the two concentric cylindrical shells. The use of spiralling baffles combined with a reduced pitch angle of the spiralled baffle plates gives an option of increasing the residence time of hydrocarbons and the catalyst in the riser channel at a given level of the reactor. In certain cases, the baffles may be necessary as stiffeners of the reactor structure. Alternatively, the same result is obtained by constructing the reactor riser space from a plurality (e.g., 6-20) of axially aligned parallel tubes which are arranged equidistantly spaced in a circular fashion.

[0036] As is evident from the discussion above, the term "axially annular cross section" used in the context of the present invention must be understood to include all the possible embodiments in which the elements that form the cross section of the reactor riser to be arranged at least essentially along the perimeter of an axially annular reactor riser. The reactor axial cross section need not necessarily have the shape of a continuous circle, while this embodiment is considered advantageous. More precisely: an axially annular reactor riser comprises a space of axially annular cross section which may be contiguous or divided by, e.g., baffle plates or tubes into axially parallel, upward running riser segments.

[0037] To the upper section of the reactor riser is connected a multiport cyclone serving as the solids separating unit which removes particulate matter from the reaction product flow. In such a cyclone, the solids suspension to be processed is admitted via a plurality of inlet ports into the cyclone chamber. The inlet ports may be symmetrically or asymmetrically spaced from each other along a circle about the vertical axis. Advantageously, the ports are arranged in a symmetrical fashion, since the reactor riser channel has an axially annular cross section, which means that the flow pattern over the cross section of the riser channel is uniform. Herein, the cyclone is provided with vanes which generate the vortex required for centrifugal separation. Generally, the vanes are arranged in a circular fashion about the perimeter of the cyclone chamber so as to form a louver which provides a number of parallel gas inlet ports.

[0038] The invention offers significant benefits. Accordingly, the multiport cyclone adapted above the axially annular reactor riser gives essential advantages in flow dynamics and process engineering over conventional arrangements and generally used single-port cyclones. Now, the cyclone can be constructed in a similar fashion as a conventional multiport cyclone, however, most advantageously using an annular louvered inlet, whereby a maximum portion of the annular inlet port area is available for admitting the gas-suspended solids flow. Later in the text will be elucidated the principal benefits of the construction according to the invention that are provided by both the riser with the axially annular cross section and the multiport cyclone connected thereto.

[0039] As noted above, the lateral mixing of solids in the apparatus according to the invention occurs over a shorter distance than in a conventional tubular riser. Resultingly, temperature and concentration differences are equalized rapidly and in a more homogenous fashion than in tubular reactors, which is an important design target in chemical fluidized-bed reactors. As an example, it may be noted herein that in a full-scale axially annular riser with an outer diameter of about 1.67 m and an inner diameter of about 1.35 m, whereby the lateral mixing distance is 160 mm. By contrast, a tube riser of the same cross-sectional area (0.76 m²) has a tube inner diameter (lateral mixing distance) of 983 mm, which is six-fold. Here, if a smaller lateral mixing distance of the tube reactor is desirable, the reactor height must be increased substantially.

[0040] Owing to the small lateral mixing distance, the feed flow over the cross-section of the reactor can be made uniform. Also the prefluidization zone, in which the flow is stabilized prior to the feed point, can be made shallower due to the above-described reason.

[0041] It can be further noted that the axially annular riser according to the invention operates at a smaller flow velocity than a tubular riser, which reduces the erosion of structural materials in the reactor and makes scaling of equipment size easier and more successful. In addition, the equipment may be implemented with a lower height, whereby problems associated with structural design and thermal expansion are alleviated.

[0042] According to a preferred embodiment, the apparatus according to the invention may comprise an inner reactor

having a riser space of axially annular cross section formed between two concentric cylindrical shells and a surrounding outer regenerator in which the contaminated catalytic solids or cooled heat transfer particulates can be regenerated for return to the process. Obviously, the reaction space concept according to the invention may be applied to varied processes and also combined with regenerator constructions different from that described above. However, the regenerator embodiment discussed herein is particularly advantageous as the distances of solids lateral travel are shortened significantly and even a large regenerator can be implemented with a short height in regard to its diameter, whereby a smaller footprint is required, the thermal expansion problems of the regenerator are reduced essentially and the reactor-regenerator construction forms a compact, stiff and easy-to-install entity.

[0043] The construction according to the invention overcomes erosion problems by flow design methods: in a multiport cyclone the solids suspension flow is incident on the cyclone inner surface as a number of small solids jets instead of entering as a single high-impact solids flow, whereby erosion of structures is smaller and smoother. A cyclone connected to a reactor according to the invention may have its height reduced to half the volume of a standard cyclone (resulting in halved residence time), because the novel cyclone due to its improved flow dynamics can be dimensioned shallower (owing to the narrow inlet ports).

[0044] Due to the multiport construction, the cyclone inlet ports can be made narrow, whereby the catalyst layer becomes shallow, and the flow velocity at the inlet port may be essentially smaller than in conventional single-port cyclones in which reduction of the inlet port width would require an increased channel height, resulting in a higher cyclone and making the communicating channel longer and clumsy in shape. The possibility of using a reduced cyclone inlet flow velocity contributes to a further lowered erosion rate, which is dependent on the flow velocity by a power of 4 to 5.

[0045] In an FCC preseparation cyclone, tests have shown the gas residence time to be in the order of 1.0 - 2.0 s, from the riser top to the cyclone outlet, after which the reaction product will further stay in the separation vessel at an elevated temperature for 5 - 40 s. During this time, valuable compounds will be lost as a consequence of chemical reactions. By contrast, the construction according to the present invention offers an exactly controllable reaction time as the catalyst enters the cyclone simultaneously from each point of the riser top. When required, the product can be cooled immediately at the exit point of the cyclone outlet nozzle and no separation vessel is needed.

[0046] The fact that a multiport cyclone achieves a vastly improved separation efficiency over a conventional cyclone is also evident from the following example:

[0047] In tests carried out at room temperature, a cyclone of 465 mm diameter with full-area inlet ports and straight vanes, the separation efficiency was 99.99 % at 5.6 m/s inlet flow velocity when the cross-sectional mass flow rate of the catalyst was over 200 kg/m²s. In a conventional Zenz cyclone with compatible dimensions and flow rates, the separation efficiency was 99.10 % computed by particle size fractions. A comparison of these separation efficiencies makes it clear that the novel cyclone with multiple narrow inlet ports according to the invention offers a superior efficiency when the design goal is to avoid high flow velocities leading to erosion.

[0048] Details of the structures used in the apparatuses according to the invention will be evident from the appended drawings. In the following detailed description, the circulating solids are denoted by abbreviation "CS" and the example process is catalytic cracking using a liquid hydrocarbon as the feed.

[0049] Referring to Fig. 1, a preferred embodiment of the apparatus according to the invention comprises two concentrically adapted cylindrical CS reactors separated by an intermediate shell 22, of which the inner will later be called the "reactor" and the outer the "regenerator".

[0050] The reactor unit is made from three concentrically mounted, essentially cylindrical tubes 1, 2 and 3, whose intertube spaces form spaces 20, 19 and 13 of axially annular cross section. Among these, the desired reaction is carried out in the space 13. The tubes which are made from steel, for example, are mounted with their longitudinal axes aligned concentrically vertical. Above the axially annular riser space 13, as a continuation of tubes 2 and 3, is mounted a multiport cyclone 14, 17 having louvered vanes 14 fixed to its outer wall. The cyclone is provided with a center tube 21 for removal of the product gas, while transfer channels 19 and 20 are provided in the inner space of the inner steel tube 3 for removal of the solids separated from the gaseous phase in the cyclone.

[0051] Inside the reactor outer shell 3, the regenerator unit comprises three concentrically mounted, essentially cylindrical tubes 4, 5 and 6, made from steel, for example, whose intertube spaces form spaces 29, 28 and 24 of axially annular cross section. Among these, catalyst regeneration is carried out in the space 24. From inside, the pressure shell 6 is lined with an insulating material layer 7 in order to maintain the shell temperature at a reasonable level for shell strength. In a similar fashion as in the reactor, above the axially annular space 24 is mounted a multiport cyclone 25, 26, whose vanes are fixed either to the cylindrical pipe 5 or the pressure shell 6. The cyclone is provided with a center tube 30 for removal of the stack gas formed in the regenerator, while transfer channels 28 and 29 are provided by means of steel tubes 5 and 6 for removal of the solids separated from the gaseous phase in the cyclone.

[0052] The fluidization gas flow of the reactor is denoted in the diagram by reference numeral 8. The gas flow 8 enters the reaction space through a fluidization bottom 12 above which it is first mixed with the solids entering via a return channel 20 via a valve 31, and then higher in the reactor riser, with the feed flow 10 injected via spray nozzles

of feed pipes 16, whereby the feed is instantaneously vaporized under contact with the hot solids flow. The mixed gas flows 8 and 10 move in a gaseous phase along the axially annular riser 13 simultaneously carrying the entrained solids therewith into the vanes 14 of the reactor cyclone. The solids release heat into a reaction or other process occurring in the riser 13 and to the vaporization of the feed flow 10, whereby the temperature of the solids falls. From the vanes 14, the gas and entrained solids enter tangentially the interior of the inner reactor cyclone chamber 17, where the particulate matter is separated by impinging on the cyclone inner wall 18 and falling into the solids transfer channels 19 and 20. When required, a portion of the solids can be returned as an overflow back to the reactor bottom section via an axially annular channel 19. While the channel 19 is not essential to the function of the apparatus, it may in some cases be advantageous to the operation of the reaction. In the channel 20, the solids dribble downward in a dense phase, whereby the mixing of the gas flows between the reactor and the regenerator via the solids transfer channel 20 will be inhibited. The gas flow 11 entering the reactor cyclone exits the reactor via the center tube 21 of the inner cyclone. The solids flow from the reactor into the regenerator is controlled by means of a valve 31 equipped with a cylindrical control element, which is arranged mechanically movable by means of bars 32.

[0053] The regenerator is adapted about the reactor so that these units are separated from each other by a transfer channel 29 filled with solids in a dense phase. In a similar fashion with the reactor, the regenerator is located in the intershell space remaining between two cylindrical envelope surfaces formed by the apparatus shell and the reactor tube mounted inside the shell. Between said reactor tube and said outer cylindrical shell structure of the reactor is further mounted a cylindrical wall to provide said solids transfer channel 29. An oxygen-containing gas flow 9 enters the regenerator via a fluidizing distributor 23 and rises in the axially annular riser channel 24 simultaneously therewith carrying the solids into the vanes 25 of the regenerator cyclone. In the regenerator, coke possibly accumulated on the surface of the solids and organic compounds penetrated in the pores thereof are oxidized, that is, burned in the riser channel 24, whereby the solids temperature is elevated.

[0054] The regenerator cyclone chamber 26 is located above the reactor proper. In the cyclone chamber 26, the solids are separated by impinging on the cyclone wall 27 and subsequently fall into channels 28 and 29. The return channel 29 passes the solids back to the reactor. That excess portion of the solids which fails to enter the return channel will fall back to the regenerator bottom section as an overflow via the channel 28. The catalyst or similar particulate matter is advantageously kept in a fluidized state during its passage in the internal return channel, whereby a control valve is redundant. The stack gas 12 of the regenerator is removed via the central tube 30 of the regenerator cyclone. The solids dribbling slowly downward in the return channel 29 in a dense phase prevent communication between the gas spaces of the reactor and the regenerator. The solids flow rate from the regenerator to the reactor is controlled by moving the cylindrical control element of a valve 33 mechanically via bars 34 connected thereto.

[0055] Now referring to Fig. 2, the apparatus shown therein comprises an elongated reactor 41 having its longitudinal axis aligned essentially vertical. The innermost section of the reactor comprises two concentrically mounted, essentially cylindrical tubes 42 and 43, whose intertube space forms a space 50 of axially annular cross section that serves as the riser of the reactor. Above the axially annular space, as an extension of the tubes 42 and 43, is mounted a multiport cyclone 52, whose louvered vanes 63 are fixed to the outer wall thereof. The cyclone is provided with a center tube 57 for removal of the product gas, while an inner tube 43 acts as an intermediate storage silo for the contaminated catalyst separated from the gaseous phase in the cyclone and as a solids transfer channel 54. Between the outer tube 42 and the reactor shell 41 is formed a return channel 60 of axially annular cross section for the return of the regenerated catalyst. To the bottom section of the reactor outer shell 41 is connected a prefluidizing gas inlet nozzle 44 communicating with the reactor riser 50, a product gas discharge nozzle 45 connected to the cyclone center tube 57, liquid hydrocarbon infeed nozzles 46, a catalytic solids infeed nozzle 47 connected to the return channel of regenerated catalyst, and a regeneration stack gas discharge nozzle 49 through which the gas carried over from the regenerator with the regenerated catalyst is removed. To the upper section of the return channel 60 may further be connected a catalyst return chamber 61 that can be a cyclone, for instance, in which the regenerated catalyst is separated from the gas carried over with the catalyst and is redistributed uniformly into the return channel. From the transfer channel 54, the contaminated catalyst is passed via a discharge nozzle 64 into the regenerator.

[0056] The above-described reactor is used for cracking in the following manner:

[0057] The fluidization gas is passed via the nozzle 44 and the fluidizing distributor bottom 48 into the reactor riser 50 of axially annular cross section, wherein thereto is mixed first the regenerated catalyst from the return channel 60 via an opening 62 and subsequently the hydrocarbon feed 46 injected via spray nozzles. The liquid hydrocarbon feed will be vaporized instantly under contact with the hot catalyst. The catalyst releases its heat in the riser 50 into the vaporization of the liquid hydrocarbon feed and the cracking reaction, whereby its temperature falls. The mixed gas flows pass in a gaseous phase upward along the axially annular riser 50, thereby carrying the catalyst into the vanes of the reactor cyclone. From the vanes 51, the gas and the entrained catalyst particles pass tangentially into the reactor cyclone chamber 52, wherein the catalyst particles are separated by impinging on the cyclone chamber wall 53 and then fall into the contaminated catalyst collecting silo and the transfer channel 54. The contaminated catalyst can be removed from the transfer channel 54 via the discharge nozzle 64 and taken to regeneration. When required, a portion

of the contaminated catalyst may be returned via an opening 56 controlled by valve 55 back to the reactor. While the return opening 56 is not essential to the function of the reactor, in some cases a partial return of contaminated catalyst to the reactor may promote the reaction. In the transfer channel 54, the contaminated catalyst moves downward in a dense phase, whereby communication between the gas flows of the reactor and the regenerator via the catalyst transfer channel 54 is prevented. Gases are removed from the reactor cyclone via the cyclone center tube 57 and the nozzle 45. The catalyst flow entering the reactor from the regenerator via the nozzle 47 passes along the return channel 60. If the catalyst flow is in fluidized state, the gas carried over is separated from the catalyst in the catalyst return chamber 61. The catalyst flow into the reactor via the opening 62 is controlled by means of the valve 58. The valve 58 having a cylindrical control element is mechanically moved via bars 59 connected thereto. In some applications, the mechanical valves can be replaced by pneumatic valves.

[0058] The reactor according to the invention can be used in the following reactions and others:

Catalytic cracking	
Reaction	Endothermic
Process temperature	520 - 650 °C
Reaction time	0.5 - 5 s
Catalyst	Conventional or latest FCC catalysts
Feed	Light gas oil, heavy gas oil, light bottom oils
Products	Light olefins, gasoline

Thermal cracking	
Reaction	Endothermic
Process temperature	650 - 950 °C
Reaction time	0.2 - 0.5 s
Solids	Inert particulate matter, possibly with catalytic properties
Feed	Bottom oils, other heavy hydrocarbon-containing feeds with a substantial content of volatile fractions
Products	Light olefins, gasoline, gas oils

Dehydrogenation	
Reaction	Endothermic
Process temperature	600 - 750 °C (about 650 °C for C ₄ , about 700 °C for C ₃ , about 750 °C for C ₂)
Reaction time	0.4 - 2 s
Solids	Dehydrogenation catalyst: type Cr-Al ₂ O ₃ , V-Ca or V-Zr
Feed	Isobutane, n-butane, propane, ethane
Products	Isobutene, butenes, propene, ethene

Oxidative dimerization of methane	
Reaction	Exothermic
Process temperature	800 - 900 °C
Reaction time	0.08 - 0.3 s
Solids	Zr-La-Sr, La ₂ O ₃ -CaO
Feed	Natural gas, oxygen
Products	Ethene

Gasification	
Reaction	Exothermic or autothermic
Process temperature	1000 - 1300 °C (thermal partial oxidation) 700 - 1000 °C (catalytic partial oxidation)

(continued)

Gasification	
Pressure	10 - 40 bar (thermal partial oxidation) 1 - 10 bar (catalytic partial oxidation)
Feed	Hydrocarbon-containing material, e.g., natural gas, coal, bottom oil and/or biomass
Products	Hydrogen and carbon-monoxide-containing synthesis gas

Claims

1. A method of converting hydrocarbons, in which method

- a gaseous or liquid hydrocarbon feed is passed into a circulating fluidized-bed reactor, wherein the feed is converted at a high temperature under the influence of particulate matter kept in a fluidized state, and
- the converted hydrocarbon products are removed from the reactor in a gaseous phase,

characterized in that

- a circulating fluidized-bed reactor (1-3; 41-43) is used having an axially annular cross section and being equipped with a multi-inlet cyclone (14, 17; 52, 63) for the separation of the particulate matter from the gas-phase reaction products, said multi-inlet cyclone being located directly above the axially annular reactor.
2. A method as defined in claim 1, **characterized in that** the reaction space comprises an intershell riser space (13; 50) formed between two concentrically located cylindrical and/or conical envelope surfaces.
3. A method as defined in claim 1 or 2, **characterized in that** the residence time of said process is 0.05 - 10 s.
4. A method as defined in any of foregoing claims 1 - 3 for separating particulate matter from gas-phase reaction products, **characterized in that** a multi-inlet cyclone is used equipped with louvered vanes (14;63).
5. A method as defined in any of foregoing claims 1 - 4, **characterized in that** catalytic cracking is performed on a feed containing light gas oil, heavy gas oil and/or light bottom oil, at a process temperature of 520 - 650 °C using 0.5 - 5 s residence time, for the purpose of preparing light olefins such as propene, butenes or amylenes and/or gasoline.
6. A method as defined in claim 5, **characterized in that** the contaminated catalyst is transferred from the reactor to a regenerator for regeneration and then returned from the regenerator back to the reactor after the regeneration step.
7. A method as defined in claim 6, **characterized in that** the contaminated catalyst is regenerated in another circulating fluidized-bed reactor of axially annular cross section and being adapted concentric with the reactor used for converting the hydrocarbon feed.
8. A method as defined in any of foregoing claims 1 - 4, **characterized in that** thermal cracking is performed on a feed containing bottom oil and/or other heavy hydrocarbon-containing feed with a substantial content of volatile fractions at a process temperature of 650 - 950 °C, using 0.2 - 0.5 s residence time, for the purpose of preparing lighter hydrocarbons.
9. A method as defined in any of foregoing claims 1 - 4, **characterized in that** dehydrogenation is performed on a feed containing pentanes, isobutane, n-butane, propane and/or ethane at a process temperature of 500 - 750 °C, using 0.4 - 2 s residence time, for the purpose of preparing amylenes, isobutene, butenes, propene or ethene, respectively.
10. A method as defined in any of foregoing claims 1 - 4, **characterized in that** oxidation of natural gas with oxygen is performed at a process temperature of 800 - 900 °C, using 0.08 - 0.3 s residence time, for the purpose of dimerizing methane.

11. A method as defined in any of foregoing claims 1 - 4, **characterized in that** thermal or catalytic gasification is performed on a hydrocarbon-containing feed at a process temperature of 700 - 1300 °C for the purpose of preparing synthesis gas.

12. A reactor for converting hydrocarbons under the influence of hot, fluidized-state particulate matter, said reactor comprising

- a reaction space (13; 50) having an at least essentially upright aligned longitudinal axis,
- connected to the bottom section of said reaction space (13; 50), a nozzle (8; 44) via which a prefluidizing gas can be passed into the reactor,
- a fluidizing distributor bottom (12; 48) via which the prefluidizing gas can be passed into the reaction space,
- connected to said reaction space (13; 50), a first set of infeed nozzles (31; 52) via which into the prefluidizing gas flow can be fed particulate matter that forms a fluidized flow,
- connected to the bottom section of said reaction space, a second set of infeed nozzles (10; 46) via which the hydrocarbon material to be treated can be fed into the reaction space so that said material is rapidly mixed in the reaction space (13; 50) with the upward flow of said prefluidizing gas and fluidized particulate matter, and, under the high temperature prevailing in said reaction space, said hydrocarbon will become converted,
- adapted to the upper end of said reaction space (13; 50), separation means (14, 17; 52, 63) for separating said particulate matter from the reaction gases, and
- a reaction gas discharge nozzle (30; 45) for removal of the product gas from the reactor,

characterized in that

- said reaction space (13; 50) is formed by a riser space of axially annular cross section, and
- said particulate matter separation means (14, 17; 52, 63) is a multi-inlet cyclone.

13. A reactor as defined in claim 12, **characterized in that** said riser space (13; 50) of axially annular cross section comprises an intershell riser space formed between two concentrically located cylindrical and/or conical envelope surfaces.

14. A reactor as defined in claim 12 or 13, **characterized in that** said riser space (13; 50) is divided by partitioning baffles into parallel flow segments.

15. A reactor as defined in claim 14, **characterized in that** said parallel flow segments are formed by spanning between said two concentrically mounted cylindrical envelope surfaces baffle plates which are essentially or exactly aligned parallel to the longitudinal axis of the reactor.

16. A reactor as defined in claim 15, **characterized in that** said baffle plates are adapted to run in a spiralling manner along the longitudinal axis or the reactor riser.

17. A reactor as defined in claim 14, **characterized in that** the reactor riser space of essentially axially annular cross section is formed by parallel tubes equidistantly spaced in a circular fashion.

18. A reactor as defined in any of claims 12 - 17, **characterized in that** the vanes (14; 63) of the cyclone are adapted in a circularly louvered fashion about the perimeter of the cyclone chamber (17; 52), partially or entirely inside the riser channel, so as to act as a louver capable of forming a plurality of parallel inlet channels for the entering gas flow.

19. A reactor as defined in any of claims 12 - 18, **characterized in that** said cyclone (14, 17) has a downward directed center tube (21).

20. A reactor as defined in claims 12 - 19, **characterized in that** said reactor (13) is connected by means of an annular channel (20) to a regenerator (24) of axially annular cross section concentrically surrounding said reactor space.

21. A reactor as defined in claim 20, **characterized in that** said regenerator channel (24) of axially annular cross section is formed by the intershell riser space remaining between two cylindrical or conical shells.

Patentansprüche

1. Verfahren zum Umwandeln von Kohlenwasserstoffen, wobei bei diesem Verfahren

- ein gasförmiger oder flüssiger Kohlenwasserstoffeintrag in einen Reaktor mit zirkulierender Wirbelschicht geleitet wird, wobei der Eintrag bei hoher Temperatur unter dem Einfluß vom Partikelmaterial, das in einem fluidisierten Zustand gehalten wird, umgewandelt wird, und
- die umgewandelten Kohlenwasserstoffprodukte aus dem Reaktor in eine Gasphase entfernt werden

dadurch gekennzeichnet, daß

- ein Reaktor (1-3; 41-43) mit zirkulierender Wirbelschicht, der einen axial ringförmigen Querschnitt aufweist und mit einem Zyklon mit mehreren Einlässen (14, 17; 52, 63) zur Abtrennung des Partikelmaterials von den Gasphasenreaktionsprodukten ausgestattet ist, wobei der Zyklon mit mehreren Einlässen direkt über dem axial ringförmigen Reaktor angeordnet wird, verwendet wird.

2. Verfahren gemäß Anspruch 1, **dadurch gekennzeichnet, daß** der Reaktionsraum einen Zwischen-Mantel-Steigrohrraum (13; 50), der zwischen zwei konzentrisch angeordneten zylindrischen und/oder konischen Hüllflächen gebildet ist, umfaßt.

3. Verfahren gemäß Anspruch 1 oder 2, **dadurch gekennzeichnet, daß** die Verweilzeit bei dem Verfahren 0,05 - 10 s beträgt.

4. Verfahren gemäß einem der vorhergehenden Ansprüche 1-3 zum Abtrennen von Partikelmaterial von Gasphasenreaktionsprodukten, **dadurch gekennzeichnet, daß** ein Zyklon mit mehreren Einlässen, der mit Lamellenblättern (14; 63) versehen ist, verwendet wird.

5. Verfahren gemäß einem der vorhergehenden Ansprüche 1-4, **dadurch gekennzeichnet, daß** das katalytische Cracken mit einem Eintrag, der leichtes Gasöl, schweres Gasöl und /oder leichtes Bodenöl enthält, bei einer Verfahrenstemperatur von 520-650°C unter Verwendung einer Verweilzeit von 0,5 - 5 s zum Zwecke der Herstellung von leichten Olefinen wie beispielsweise Propen, Butene oder Amylene und/oder Gasolin durchgeführt wird.

6. Verfahren gemäß Anspruch 5, **dadurch gekennzeichnet, daß** der kontaminierte Katalysator aus dem Reaktor zu einem Regenerator zur Regeneration überführt und dann von dem Regenerator nach dem Regenerationsschritt zu dem Reaktor zurückgeführt wird.

7. Verfahren gemäß Anspruch 6, **dadurch gekennzeichnet, daß** der kontaminierte Katalysator in einem anderen Reaktor mit zirkulierender Wirbelschicht mit axial ringförmigem Querschnitt regeneriert wird und der konzentrisch an den Reaktor, der für die Umwandlung des Kohlenwasserstoffeintrags verwendet wird, angepaßt ist.

8. Verfahren gemäß einem der vorhergehenden Ansprüche 1-4, **dadurch gekennzeichnet, daß** das thermische Cracken mit einem Eintrag, der Bodenöl und/oder anderen schweren Kohlenwasserstoff-haltigen Eintrag mit einem wesentlichen Gehalt an flüchtigen Fraktionen enthält, bei einer Verfahrenstemperatur von 650-950°C unter Verwendung einer Verweilzeit von 0,2 - 0,5 s zum Zwecke der Herstellung von leichteren Kohlenwasserstoffen durchgeführt wird.

9. Verfahren gemäß einem der vorhergehenden Ansprüche 1-4, **dadurch gekennzeichnet, daß** die Dehydrogenierung mit einem Eintrag, der Pentane, Isobutan, n-Butan, Propan und/oder Ethan enthält, bei einer Verfahrenstemperatur von 500-750°C unter Verwendung einer Verweilzeit von 0,4 - 2 s zum Zwecke der Herstellung von Amylenen, Isobuten, Butene, Propen bzw. Ethen durchgeführt wird.

10. Verfahren gemäß einem der vorhergehenden Ansprüche 1-4, **dadurch gekennzeichnet, daß** die Oxidation von Erdgas mit Sauerstoff bei einer Verfahrenstemperatur von 800-900°C unter Verwendung einer Verweilzeit von 0,08-0,3 s zum Zwecke der Dimerisierung von Methan durchgeführt wird.

11. Verfahren gemäß einem der vorhergehenden Ansprüche 1-4, **dadurch gekennzeichnet, daß** die thermische oder katalytische Vergasung mit Kohlenwasserstoffhaltigem Eintrag bei einer Verfahrenstemperatur von 700-1300°C zum Zwecke der Herstellung von Synthesegas durchgeführt wird.

12. Reaktor zum Umwandeln von Kohlenwasserstoffen unter dem Einfluß von heißem, fluidisiertem Partikelmaterial, wobei der Reaktor umfaßt

- einen Reaktionsraum (13; 50) mit einer wenigstens im wesentlichen aufrecht ausgerichteten Längsachse,
- verbunden mit dem Bodenbereich des Reaktionsraums (13; 50), eine Düse (8; 44), über die ein vorfluidisiertes Gas in den Reaktor geleitet werden kann,
- einen fluidisierenden Verteilerboden (12; 48), über den das vorfluidisierte Gas in den Reaktionsraum geleitet werden kann,
- verbunden mit dem Reaktionsraum (13; 50), einen ersten Satz von Eintragsdüsen (31; 52), über die in den vorfluidisierten Gasstrom Partikelmaterial eingetragen werden kann, das eine fluidisierte Strömung bildet,
- verbunden mit dem Bodenabschnitt des Reaktionsraumes, einen zweiten Satz von Eintragsdüsen (10; 46), über die das zu behandelnde Kohlenwasserstoffmaterial in den Reaktionsraum eingebracht werden kann, so daß das Material in dem Reaktionsraum (13; 50) mit dem Aufwärtsstrom des vorfluidisierten Gases und dem fluidisiertem Partikelmaterial schnell gemischt wird, und unter der hohen Temperatur, die in dem Reaktionsraum vorherrscht, der Kohlenwasserstoff umgewandelt wird,
- angepaßt an das obere Ende des Reaktionsraumes (13; 50), Abtrennungsmittel (14, 17; 52, 63) zum Abtrennen von Partikelmaterial aus den Reaktionsgasen, und
- eine Reaktionsgas Ausgasedüse (30; 45) zum Entfernen des Produktgases aus dem Reaktor,

dadurch gekennzeichnet, daß

der Reaktionsraum (13; 50) durch einen Steigrohrraum mit axial ringförmigem Querschnitt gebildet ist, und das Abtrennungsmittel (14, 17; 52, 63) für Partikelmaterial ein Zyklon mit mehreren Einlässen ist.

13. Reaktor gemäß Anspruch 12, **dadurch gekennzeichnet, daß** der Steigrohrraum (13; 50) mit axial ringförmigem Querschnitt einen Zwischen-Mantel-Steigrohrraum, der zwischen zwei konzentrisch angeordneten zylindrischen und/oder konischen Hüllflächen gebildet ist, umfaßt.

14. Reaktor gemäß Anspruch 12 oder 13, **dadurch gekennzeichnet, daß** der Steigrohrraum (13; 50) durch Trennbleche in parallele Strömungsabschnitte unterteilt ist.

15. Reaktor gemäß Anspruch 14, **dadurch gekennzeichnet, daß** die parallelen Strömungsabschnitte durch Spannen von Ablenkblechen, die im wesentlichen oder genau parallel zu der Längsachse des Reaktor ausgerichtet sind, zwischen den zwei konzentrisch angeordneten zylindrischen Hüllflächen.

16. Reaktor gemäß Anspruch 15, **dadurch gekennzeichnet, daß** die Ablenkbleche ausgelegt sind, um spiralartig entlang der Längsachse oder des Reaktor-Steigrohres zu verlaufen.

17. Reaktor gemäß Anspruch 14, **dadurch gekennzeichnet, daß** der Reaktor-Steigrohrraum mit im wesentlichen axial ringförmigem Querschnitt durch parallele Röhren, die in einem zirkularen Muster äquidistant beabstandet sind, gebildet ist.

18. Reaktor gemäß einem der Ansprüche 12-17, **dadurch gekennzeichnet, daß** die Blätter (14; 63) des Zyklons in einem zirkularen Lamellen-Muster entlang der äußeren Begrenzung der Zyklonkammer (17; 52), teilweise oder vollständig innerhalb des Steigrohrkanals, um so als Lamellen zu wirken, die geeignet sind, eine Vielzahl von parallelen Einlaßkanälen zum Einlassen des Gasstroms zu bilden, angepaßt sind.

19. Reaktor gemäß einem der Ansprüche 12-18, **dadurch gekennzeichnet, daß** der Zyklon (14, 17) eine nach unten gerichtete zentrale Röhre (21) aufweist.

20. Reaktor gemäß Ansprüchen 12-19, **dadurch gekennzeichnet, daß** der Reaktor (13) mittels eines ringförmigen Kanals (20) mit einem Regenerator (24) mit axial ringförmigem Querschnitt, der den Reaktorraum konzentrisch umgibt, verbunden ist.

21. Reaktor gemäß Anspruch 20, **dadurch gekennzeichnet, daß** der Regeneratorkanal (24) mit axial ringförmigem Querschnitt durch den Zwischen-Mantel-Steigrohrraum, der zwischen zwei zylindrischen oder konischen Mänteln verbleibt, gebildet wird.

Revendications

1. Procédé pour la conversion d'hydrocarbures, dans lequel procédé

- 5 - une charge hydrocarbonée gazeuse ou liquide est envoyée dans un réacteur à lit fluidisé en circulation, dans lequel la charge est convertie à une haute température sous l'influence de matière particulaire maintenue à l'état fluidisé, et
- les produits hydrocarbonés convertis sont éliminés du réacteur dans une phase gazeuse,

10 **caractérisé en ce que**

- il est utilisé un réacteur à lit fluidisé en circulation (1-3 ; 41-43) qui a une section droite annulaire axialement et est équipé d'un cyclone multi-entrée (14, 17 ; 52, 63) pour la séparation de la matière particulaire des produits de réaction en phase gazeuse, ledit cyclone multi-entrée étant situé directement au-dessus du réacteur annulaire axialement.

2. Procédé suivant la revendication 1, **caractérisé en ce que** l'espace de réaction comprend un espace de montée inter-enveloppe (13 ; 50) formé entre deux surfaces d'enveloppes cylindriques et/ou coniques disposées de façon concentrique.

3. Procédé suivant les revendications 1 ou 2, **caractérisé en ce que** le temps de séjour dudit procédé est de 0,05 à 10 secondes.

4. Procédé suivant l'une quelconque des revendications 1 à 3 pour la séparation de matière particulaire de produits de réaction en phase gazeuse, **caractérisé en ce qu'il** est utilisé un cyclone multi-entrée équipé d'ailettes à lumières (14 ; 63).

5. Procédé suivant l'une quelconque des revendications 1 à 4, **caractérisé en ce qu'un** craquage catalytique est réalisé sur une charge contenant un gasoil léger, un gasoil lourd et/ou une huile de queue légère, à une température de traitement de 520°C à 650°C avec un temps de séjour de 0,5 à 5 secondes, dans le but de préparer des oléfines légères comme le propène, les butènes ou les amylènes et/ou de l'essence.

6. Procédé suivant la revendication 5, **caractérisé en ce que** le catalyseur contaminé est transféré du réacteur vers une unité de régénération pour la régénération et ensuite renvoyé de l'unité de régénération vers le réacteur après l'étape de régénération.

7. Procédé suivant la revendication 6, **caractérisé en ce que** le catalyseur contaminé est régénéré dans un autre réacteur à lit fluidisé en circulation à section droite annulaire axialement et disposé de façon concentrique par rapport au réacteur utilisé pour la conversion de la charge hydrocarbonée.

8. Procédé suivant l'une quelconque des revendications 1 à 4, **caractérisé en ce qu'un** craquage catalytique est réalisé sur une charge contenant une huile de queue et/ou une autre charge contenant des hydrocarbures lourds ayant une teneur substantielle en fractions volatiles, à une température de traitement de 650°C à 950°C avec un temps de séjour de 0,2 à 0,5 seconde, dans le but de préparer des hydrocarbures plus légers.

9. Procédé suivant l'une quelconque des revendications 1 à 4, **caractérisé en ce qu'une** déshydrogénation est réalisée sur une charge contenant des pentanes, de l'isobutane, du n-butane, du propane et/ou de l'éthane, à une température de traitement de 500°C à 750°C avec un temps de séjour de 0,4 à 2 secondes, dans le but de préparer des amylènes, de l'isobutène, des butènes, du propène ou de l'éthène, respectivement.

10. Procédé suivant l'une quelconque des revendications 1 à 4, **caractérisé en ce qu'une** oxydation de gaz naturel par de l'oxygène est réalisée à une température de traitement de 800°C à 900°C avec un temps de séjour de 0,08 à 0,3 seconde, dans le but de dimériser le méthane.

11. Procédé suivant l'une quelconque des revendications 1 à 4, **caractérisé en ce qu'une** gazéification thermique ou catalytique est réalisée sur une charge contenant des hydrocarbures, à une température de traitement de 700°C à 1300°C dans le but de préparer un gaz de synthèse.

12. Réacteur pour la conversion d'hydrocarbures sous l'influence d'une matière particulaire chaude à l'état fluidisé, ledit réacteur comprenant :

- un espace de réaction (13 ; 50) ayant au moins un axe longitudinal essentiellement aligné verticalement,
- une buse (8 ; 44) reliée à la section inférieure dudit espace de réaction (13 ; 50), par laquelle buse un gaz de préfluidisation peut être envoyé dans le réacteur,
- un fond distributeur fluidisant (12 ; 48) par lequel le gaz de préfluidisation peut être envoyé dans l'espace réactionnel,
- un premier jeu de buses d'introduction de charge (31 ; 52) relié audit espace réactionnel (13 ; 50), par lesquelles peut être introduite dans le courant de gaz de préfluidisation une matière particulaire qui forme un écoulement fluidisé,
- un second jeu de buses d'introduction de charge (10 ; 46) relié à la section inférieure dudit espace réactionnel par lesquelles la matière hydrocarbonée à traiter peut être introduite dans l'espace réactionnel de telle sorte que ladite matière est rapidement mélangée dans l'espace réactionnel (13 ; 50) avec l'écoulement ascendant dudit gaz de préfluidisation et de matière particulaire fluidisée, et que dans les hautes températures régnant dans ledit espace réactionnel, ledit hydrocarbure est converti,
- un moyen de séparation (14, 17 ; 52, 63) disposé à l'extrémité supérieure dudit espace réactionnel (13 ; 50), pour séparer ladite matière particulaire des gaz de réaction, et
- une buse de décharge des gaz de réaction (30 ; 45) pour l'élimination des gaz produits du réacteur,

caractérisé en ce que

- ledit espace réactionnel (13 ; 50) est formée par un espace de montée de section droite annulaire axialement, et
- ledit moyen de séparation de matière particulaire (14, 17 ; 52, 63) est un cyclone multi-entrée.

13. Réacteur suivant la revendication 12,

caractérisé en ce que ledit espace de montée (13 ; 50) de section droite annulaire axialement comprend un espace de montée inter-enveloppe formé entre deux surfaces d'enveloppes cylindriques et/ou coniques disposées de façon concentrique.

14. Réacteur suivant les revendications 12 ou 13,

caractérisé en ce que ledit espace de montée (13 ; 50) est divisé par des chicane de séparation en segments à écoulements parallèles.

15. Réacteur suivant la revendication 14,

caractérisé en ce que lesdits segments à écoulements parallèles sont formés par l'installation entre lesdites surfaces d'enveloppes cylindriques montées de façon concentrique, de plaques de chicane qui sont essentiellement ou exactement alignées parallèlement à l'axe longitudinal du réacteur.

16. Réacteur suivant la revendication 15,

caractérisé en ce que lesdites plaques de chicane sont disposées de façon à suivre un chemin en spirale le long de l'axe longitudinal ou de l'espace de montée du réacteur.

17. Réacteur suivant la revendication 14,

caractérisé en ce que l'espace de montée du réacteur de section droite essentiellement annulaire axialement est formé par des tubes parallèles équidistants disposés de façon circulaire.

18. Réacteur suivant l'une quelconque des revendications 12 à 17, **caractérisé en ce que** les ailettes (14 ; 63) du cyclone sont disposées de façon à former des lumières selon un cercle le long du périmètre de la chambre du cyclone (17 ; 52), partiellement ou entièrement à l'intérieur du canal de montée, de façon à jouer le rôle de lumière capable de former une pluralité de canaux d'entrée parallèles pour l'écoulement du gaz entrant.

19. Réacteur suivant l'une quelconque des revendications 12 à 18, **caractérisé en ce que** ledit cyclone (14 ; 17) a un tube central (21) dirigé vers le bas.

20. Réacteur suivant l'une quelconque des revendications 12 à 19, **caractérisé en ce que** ledit réacteur (13) est relié au moyen d'un canal annulaire (20) à une unité de régénération (24) de section droite annulaire axialement en-

tourant de façon concentrique l'espace dudit réacteur.

21. Réacteur suivant la revendication 20,
caractérisé en ce que ledit canal (24) de l'unité de régénération de section droite axialement annulaire est formé
par l'espace de montée inter-enveloppe restant entre deux enveloppes cylindriques ou coniques.

5

10

15

20

25

30

35

40

45

50

55



